

## KRI400T / KRI800T / C400 / C600



**KRI 400T / KRI 800T**



**C400 / C600**

## Cable coilers

### DESCRIPTION

Fully automatic single pan cable coiler systems for coiling wires, tubes, cables. They are equipped with a rotating plate designed with adjustable sticks for working different diameters.

The cable goes from the cutting system to the coil pins through an inserting tube. Outer and inner diameter can be programmed on the keyboard. After the coiling process the coil pins automatically retracts, the safety cover opens and the coiled cable can be removed.

### Technical features

	<b>KRI 400T/C400</b>	<b>KRI 800T</b>	<b>C600</b>
<b>Coil inner diameter:</b>	min 100 mm, max 300 mm	min 250 mm, max 600 mm	min 100, max 450 mm
<b>Coil outer diameter:</b>	max 400 mm	max 800 mm	max 600 mm
<b>Coil weight:</b>	max 40 Kg	max 80 Kg	max 60 Kg
<b>Cable/wire diameter:</b>	max 18 mm	max 35 mm	max 18 mm
<b>Speed:</b>	max 320 g/m	max 133 g/m	max 250 g/m
<b>Power supply:</b>	220 V / 50 Hz / 1000 VA		
<b>Air suppli:</b>	6 bar		
<b>Dimensioni:</b>	680 x 720 x 1130 mm	1230 x 1060 x 1260 mm	750 x 850 x 1130 mm
<b>Weight:</b>	105 Kg	225 Kg	150 Kg

**CE Conformity:** Cable coilers KRI 400T, KRI 800T, C400 e C600 fully comply with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.

**Important:** Mecatronic recommends to submit samples in case of doubt about the processing capabilities of a particular machine.

---

Technical specifications are subject to change according to possible needs and without notice

---