

MINI



MINI-LA.C



MINI-LO.M



MINI-PNEUM. LA.C



MINI-PNEUM. LO.C

MECATRONIC
Miniapplicators

FEATURES

The MINI – LATERAL CAM and the MINI - LONGITUDINAL MICROMETRIC are extremely versatile miniapplicators, designed for processing frontal and lateral banded terminals with open or closed contact.

They are equipped with a non resetable piece counter to better manage the preventive maintenance and the run out of the wear parts. They work either with present or absent terminal simply turning a cam.

Standard piece counter in Micrometric version, Cam version optional

Available versions: Lateral and Longitudinal Cam – Micrometric – Pneumatic Cam

Technical specifications

	MINI-LA.C/LA.M	MINI-LO.C/LO.M	MINI-PNEUM-LA.C.	MINI-PNEUM-LO.C.
Vertical stroke:	40mm			
Carrier stroke:	Max 36mm		Max 40mm	
Crimping height:	135.8mm			
Dimensions:	149x112x144 mm	149x71x160 mm	149x118x224 mm	149x71x226 mm
Weight:	4,9 Kg	5,6 Kg	5,1 Kg	5,5 kg
Micrometric adjustment Minimum pitch:	0.03mm/release		cam	0.03mm/release

CE - Conformity: MINI fully complies with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.

Important note: Mecatronic recommends that wire samples be submitted in cases where there is doubt as to the processing capabilities of a particular machine.

Technical specifications are subject to change according to possible needs and without notice.